

TURN CHILD SAFETY INTO CHILD'S PLAY

LOCINOX[®]
Let's make it better together



Your complete solution for
swimming pools, playgrounds,
parks, and garden gates

FULL OPTION CHILD-SAFETY

FORTIMA • CARACAL • SERVAL

The combination of the child-safe latch FORTIMA, the CARACAL gate closer and the SERVAL self-closing hinge, offers you the solution for both public and private pools.

The 3 product combo assures you a closed gate at all times. CARACAL guarantees a damped closing in accordance with the chosen speed settings. The extra spring force in the SERVAL helps the CARACAL to close the gate even when subjected to wind load. The magnetic functionality of the FORTIMA attracts the lock side of the gate once it approaches the keep side with a force that is twice as big as the standard.

The robust built of the products guarantees a worry-free use and functioning.

Install the NOSTEP on top of the SERVAL to eliminate kids using the SERVAL as a step to climb over the gate.

Install the FORTIMA at least 54" above the ground and it forms a physical barrier that restricts access by unsupervised children under the age of 5.



FORTIMA

MAGNETIC CHILD-SAFE LATCH

The FortiMa is a magnetic child-safe gate latch that avoids kids entering or leaving zones where they shouldn't come unsupervised. The handle is mounted at a height where a child cannot reach. A technical ingenuity avoids the magnet being opened by any push down force.

MORE INFO



Before installing, always confirm any safety compliance requirements with the respective authorities

WHAT MAKES IT SPECIAL?

- Strongest magnetic force on the market
- Sag-proof
- Pool Code Compliant
- Rekeyable to match any lock
- Easy installation

FEATURES

Gate type:	Left & right single leaf gate Metal, vinyl or wooden gates
Posts:	Round* and square
Housing:	Anodized aluminium
Cylinder:	Rekeyable to match any lock Schlage-C Key-in-knob cylinder (5pin, drilled 6pin)
Magnetic distance:	1-1/4"
Mounting:	At least 54" above ground
Fixation:	Quick-fix, self drilling screws
Adjustability:	Horizontal: 1" Gap: 3/8" - 1-3/8"
Weather resistance:	-22°F → +158°F
Color:	RAL 9005
Warranty:	Limited Lifetime
Tested:	Up to 2 million cycles

* Brackets available for round posts




CARACAL

HYDRAULIC 180° GATE CLOSER

The Caracal is a compact gate closer which allows soft and easy opening and guarantees a damped closing according to the desired speed settings. It is a perfect fit for swimming pools, playgrounds, parks, and garden gates.



MORE INFO



WHAT MAKES IT SPECIAL?

- Hydraulic damping
- Speed regulation
- Easy to open
- Flexible installation
- No welding required



Always use CARACAL in combination with SERVAL. Do not mount 2 CARACALS as the damping-ability will hamper a guaranteed closing.

FEATURES

Gate type:	Left and right turning gates Metal, vinyl or wooden gates Max width: 48"
Posts:	Round* and square
Housing:	Fiberglass reinforced polyamide
Damping:	Hydraulic
Opening angle:	180°
Closing force:	8 Nm
Closing speed:	Adjustable
Fixation:	Quick-fix or, self drilling screws
Adjustability:	Vertical: 13/16" Horizontal: 13/16"
Weather resistance:	-4°F → +140°F
Color:	RAL 9005
Warranty:	3 years
Tested:	500K cycles



* Brackets available for round posts


SERVAL

180° SPRING HINGE

The Serval is a compact spring hinge with force adjustability. The high-tech internal components, allow for perfect functionality in all weather conditions.



MORE INFO



WHAT MAKES IT SPECIAL?

- Perfect functionality in all weather conditions
- Easy and flexible installation
- No welding required



Tip: Mounting the NOSTEP anti climb device on top of the SERVAL, avoids people using it as a step to climb over the gate.

FEATURES

Gate type: Left and right turning gates
Metal, vinyl or wooden gates
Max width: 48"

Posts: Round or square

Housing: Fiberglass reinforced polyamide

Opening angle: 180°

Closing force: 6,5 Nm

Force adjustability: from 2 up to 7 Nm
(at closed position)

Fixation: Quick-fix or, self drilling screws

Adjustability: Vertical: 13/16"
Horizontal: 13/16"

Weather resistance: -22°F → +140°F

Color: RAL 9005

Warranty: 3 years

Tested: 500K cycles





Member of:



LOCINOX

Contact us for more information:
salesusa@locinox.com